


LED



LM-79 & LM-80
Accredited



COMPACT CLUSTER LED BULB
50,000 HOUR OPERATION
ENERGY EFFICIENT
75W-150W INCANDESCENT
& 70W-100W METAL HALIDE
REPLACEMENT LAMPS

Features and Applications:

- Great Energy Savings
- Rated Life 50,000 Hours
- High Power Factor –Self Ballasted
- Bright –High CRI –High Lumen Output
- Built-in Surge Suppressors & Protection
- CCT 5,500K for MH or 3,000K for HPS Replacement
- Listed to UL Standard 1598C & UL 1993

Applications:

Designed for energy saving for the following applications and more:

- Street Lighting,
- Sidewalk Lighting
- Parking Lot lighting
- Park Lighting
- Yard Lighting

**E26
Base**



Model #:	CCL-10W12-55K-E26	CCL-15W12-55K-E26	CCL-20W12-55K-E26	CCL-25W12-55K-E26	CCL-30W12-55K-E26
Power Consumption:	11W	16W	22W	26W	30W
Beam Angle:	360°	360°	360°	360°	360°
Input voltage:	100-277V	100-277V	100-277V	100-277V	100-277V
Frequency:	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
LED Engine:	Epistar	Epistar	Epistar	Epistar	Epistar
Base:	E26	E26	E26	E26	E26
Dimmable:	No	No	No	No	No
Power Factor:	>0.9	>0.9	>0.9	>0.9	>0.9
Efficiency:	100 lpw	100 lpw	100 lpw	100 lpw	100 lpw
Color Rendering Index (CRI):	>0.7	>0.7	>0.7	>0.7	>0.7
Initial Lumens:	1100 lm	1600 lm	2200 lm	2600 lm	3000 lm
Color Temperature (CCT):	5500K	5500K	5500K	5500K	5500K
Operating Temp:	-40°C ~ 45°C	-40°C ~ 45°C	-40°C ~ 45°C	-40°C ~ 45°C	-40°C ~ 45°C
Life:	>50,000 hrs	>50,000 hrs	>50,000 hrs	>50,000 hrs	>50,000 hrs
Size:	Ø2¾x5"	Ø2¾x5"	Ø2¾x6-1/4"	Ø2¾x6-7/8"	Ø2¾x7-1/4"
Warranty:	5 years	5 years	5 years	5 years	5 years