

LED



LM-79 & LM-80
Accredited



CE

RoHS



CLUSTER LED BULB 50,000 HOUR OPERATION ENERGY EFFICIENT 70W-200W MH & HPS REPLACEMENT LAMPS

Features and Applications:

- Great Energy Savings
- Rated Life 50,000 Hours
- High Power Factor –Self Ballasted
- Bright –High CRI –High Lumen Output
- Built-in Surge Suppressors & Protection
- CCT: 5,500K for MH or 3,000K for HPS Replacement
- Listed to UL Standard 1598C & UL 1993

Applications:

Designed for energy saving for the following applications and more:

- Street Lighting,
- Sidewalk Lighting
- Parking Lot lighting
- Park Lighting
- Yard Lighting

E26
Base



Model #:	CL-20W8-55K-E26	CL-30W8-55K-E26	CL-40W8-55K-E26	CL-50W8-55K-E26
Power Consumption:	25W	35W	41W	52W
Beam Angle:	360°	360°	360°	360°
Input voltage:	100-277V	100-277V	100-277V	100-277V
Frequency:	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
LED Engine:	Epistar	Epistar	Epistar	Epistar
Base:	E26	E26	E26	E26
Dimmable:	No	No	No	No
Power Factor:	>0.9	>0.9	>0.9	>0.9
Efficiency:	100 lpw	100 lpw	100 lpw	100 lpw
Color Rendering Index (CRI):	>0.7	>0.7	>0.7	>0.7
Initial Lumens:	2500 lm	3500 lm	4100 lm	5200 lm
Color Temperature (CCT):	5500K	5500K	5500K	5500K
Operating Temp:	-40°C ~ 45°C	-40°C ~ 45°C	-40°C ~ 45°C	-40°C ~ 45°C
Life:	>50,000 hrs	>50,000 hrs	>50,000 hrs	>50,000 hrs
Size:	Ø3½x6¼"	Ø3½x6¼"	Ø3½x6¼"	Ø3½x8¼"
Warranty:	5 years	5 years	5 years	5 years