

EXIT SIGNS



EDGE-LIT EXIT SIGNS



JELS-800DR-MA



JELS-800SR-CA

ELECTRICAL CHARACTERISTICS

Model #	Lamp Type	Sides	Background
JELS-800DR-MA	LED - Red "Exit"	Double Sided	Mirrored
JELS-800SR-CA	LED - Red "Exit"	Single Sided	Acrylic Clear

PACKING INFORMATION

Model #	Units Per Carton	Weight Per Carton	Cube Per Carton
JELS-800DR-MA	6 pc.	17.2 lbs.	1.0 cu.
JELS-800SR-CA	6 pc.	17.2 lbs.	1.0 cu.

FEATURES

HOUSING:

- Compact and Decorative Designs
- Rigid Aluminum Housing
- Letters 6" Height with 3/4" stroke
 - JELS-800SR-CA Model:*
 - Etched, clear acrylic edge-lit panel with removable directional indicators
 - Single face configuration
 - JELS-800DR-MA Model:*
 - Mirrored Edge-Lit Panel
 - Double Face Configuration

MOUNTING:

- Universal (Wall, Side, or Ceiling) Mounting

ELECTRICAL:

- Dual voltage operation 120/277 VAC, 60 Hz,
- Low Energy consumption—only 3 watts at 120V
- LED Indicator light and test switch

LAMPS:

- LED Lamps are operating in normal (AC input) and emergency (DC Input) modes.

BATTERY:

- Nickel-Cadmium battery (4.8V 850mA) delivers more than 3 hours capacity to emergency lamps
- 24 hours recharge after 90 minutes discharge
- Low voltage battery disconnection—preventing deep discharge damage to the battery