

## **In Situ Temperature Measurement Test Report**

For

# **DONGGUAN THAILIGHT SEMICONDUCTOR LIGHTING CO.,LTD**

**(Brand Name: THAILIGHT)**

Sanhui Ind. Area, Cunwei, Hengli, Dongguan, China.

## **Outdoor Full-Cutoff Wall-mounted Area Luminaires**

Model name(s): TLWMK12XYZZ

Remark: X=CCT(3=3000K,4=4000K,5=5000K)

YY=Mounting Option(WM=Wall Mount)

ZZ=Housing Color (use 2 digits to indicate all of color)

Representative (Tested) Model: TLWMK123WMZZ

Model Different: All construction and rating are the same, except CCT

Test & Report By:

*Johnson Sun*

Engineer: Johnson Sun

Update: Nov.16, 2016

Review By:

*Tommy Liang*

Manager: Tommy Liang

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

**Laboratory: Standard-Tech Co. Ltd Testing Center**

**NVLAP CODE: 201011-0**

Report Format Number STD/QR4918-A/0

Address: Standard-Tech Building, No.6 Guanhong Road,Guangzhou Science City, Guangzhou 510663, China

Tel: 8620-3229 0320

Fax: 8620-32290422

<http://www.standard-tech.com>

## Table of Contents

1 General . . . . .	3
1.1 Product Information . . . . .	3
1.2 Standards or methods . . . . .	4
1.3 Equipment list . . . . .	4
2 Test conducted and method . . . . .	4
2.1 Ambient Condition . . . . .	4
2.2 Temperature Stabilization . . . . .	4
2.3 Thermocouples . . . . .	5
2.4 Thermocouples contact . . . . .	5
3 Test Results . . . . .	6
3.1 Data: . . . . .	6
3.2 Test Photo: . . . . .	6

# 1 General

## 1.1 Product Information

Brand Name	THAILIGHT
Model Number	TLWMK12XYZZ
Luminaire Type	Outdoor Full-Cutoff Wall-mounted Area Luminaires
Nominal Power	12W
Rated Initial Lamp Lumen	--
Declared CCT	3000K,4000K,5000K
LED Manufacturer	Philips Lumileds
LED Model	L130-2780003000W21
Sample Receipt Date	Nov.11,2016
Sample Number	GZE161105-BF1

Photo



Laboratory: Standard-Tech Co. Ltd Testing Center

NVLAP CODE: 201011-0

Report Format Number STD/QR4918-A/0

Address: Standard-Tech Building, No.6 Guanhong Road,Guangzhou Science City, Guangzhou 510663, China

Tel: 8620-3229 0320

Fax: 8620-32290422

<http://www.standard-tech.com>

## 1.2 Standards or methods

The following standards are partly or totally used or referenced for test:

No.	Name
ANSI/UL 1598:2008	Luminaires

## 1.3 Equipment list

Equipment ID	Equipment Name	Last Calibration Date	Next Calibration Date
PF210	Power Meter	2016-07-01	2017-06-30
ST-R-181A	Temperature Tester	2016-07-01	2017-06-30

# 2 Test conducted and method

## 2.1 Ambient Condition

Test was conducted in an ambient temperature of  $25 \pm 5^{\circ}\text{C}$ . Ambient temperature variations above or below  $25^{\circ}\text{C}$  was subtracted from or added to temperatures recorded at points on the luminaire.

The ambient temperature was measured by a thermocouple which was immersed in 15ml of mineral oil in a glass container.

## 2.2 Temperature Stabilization

Temperatures were measured after they have stabilized when the test has been running for a minimum of 7.5 hours, or the test has been running for a minimum of 3 hours and three successive reading taken at 15 minutes intervals are with  $1^{\circ}\text{C}$  of another and are not rising.

## 2.3 Thermocouples

Type J thermocouple was used for temperature measurement. The thermocouple was 0.05mm<sup>2</sup>(30AWG), and complied with the requirements specified in ASTM MNL 12 and limits of error specified in NIST ITS 90 and ISA MC96.1.

## 2.4 Thermocouples contact

Thermocouples were in contact with the TMP LED location described in LM-80 test report. In order to gain the maximum temperature, if appropriate, more than one thermocouple were contact in these locations. For details information, please refer to clause 3.3 for the photo of thermocouple contact.

### 3 Test Results


Test date	2016-11-12	Test Ambient	25.1 °C
Sample No.		LED Package Model	
GZE161105-BF1		L130-2780003000W21	
LED driver of Each Lamp	Output voltage V	Measured LED working current (Max.) mA	
1	41.1	127.0	

#### 3.1 Test Data In:

Input Vol.	120.0V	Input Current	0.0990A	Input Wattage	11.78W	Temperature stabilization time:	500 min	
No.	Temperature (°C)		No.	Temperature (°C)		No.	Temperature (°C)	
	Measured	Corrected at 25°C		Measured	Corrected at 25°C		Measured	Corrected at 25°C
1	52.5	52.4	3	52.2	52.1	5	52.7	52.6
2	51.6	51.5	4	51.8	51.7	6	51.1	51.0
The highest in-situ measured temperature LED is 52.6°C								

#### 3.2 Test Photo:

Ts Position:



Laboratory: Standard-Tech Co. Ltd Testing Center

NVLAP CODE: 201011-0

Report Format Number STD/QR4918-A/0


Address: Standard-Tech Building, No.6 Guanhong Road, Guangzhou Science City, Guangzhou 510663, China

Tel: 8620-3229 0320

Fax: 8620-32290422

<http://www.standard-tech.com>

Thermocouple Location on Temperature Measurement Point (TMP):



## Results

Time (t) at which to estimate lumen maintenance (hours):	50,000
Lumen maintenance at time (t) (%):	78.90%
Reported L70 (hours):	>54000

## Results

Time (t) at which to estimate lumen maintenance (hours):	22,000
Lumen maintenance at time (t) (%):	89.86%
Reported L90 (hours):	22,000

\*\*\*\*\* END OF THE TEST REPORT\*\*\*\*\*

Laboratory: Standard-Tech Co. Ltd Testing Center

NVLAP CODE: 201011-0

Report Format Number STD/QR4918-A/0

Address: Standard-Tech Building, No.6 Guanhong Road, Guangzhou Science City, Guangzhou 510663, China

Tel: 8620-3229 0320

Fax: 8620-32290422

<http://www.standard-tech.com>