


SHATTERPROOF T8 LED GLASS LAMP TYPE B NSF COMPLIANT



Features

- Built-in 1-10V dimming driver
- Simple installation & replacement
- Safe when connect AC power to 1-10V Dimming side
- No distinction between DIM+ and DIM-
- Easily turn the lights on or off with the paddle switch and use the slide control to adjust the lights to the desired level
- Shatterproof design: Meet NSF requirements
- Certifications: UL / DLC Listed



Ordering Bar

Model	Size	Wattage	Voltage	CCT	Housing Material
JT8-B-NSF	2FT	9W	Blank (120-277V)	30K (3000K)	FG (Frosted Glass) CG (Clear Glass)
	4FT	12W		35K (3500K)	
		15W		40K (4000K)	
		18W		50K (5000K)	

Electrical Data Table

Product Series	JT8-B-NSF-9W	JT8-B-NSF-12W	JT8-B-NSF-15W	JT8-B-NSF-18W
Nominal Wattage	9W	12W	15W	18W
Size	2FT	4FT		
Average Lumen Efficacy	133 Lms/W	150 Lms/W	146 Lms/W	130 Lms/W
Average Lumens	1200 Lms	1800 Lms	2200 Lms	2350 Lms
Voltage	120-277VDC			
Base Type	G13			
Standard Control Specification	0-10V Dimming			
CRI	>83			
Power Factor	>0.90			
THD @ 120V	<20%			
Ambient Working Temperature	0°C to +40°C			
Beam Angle	320°			
Construction	Frosted & Clear Shatterproof Glass (PET Film) Options			
Lifetime	>50,000 Hours			
Warranty	5 Years			



Miami, FL USA - info@jademar.com
T: 305.640.0465 - F: 305.640.0468
WWW.JADEMAR.COM



Information contained herein is subject to change without notice.
Values are nominal. All values conform to DLC tolerances.
Revised 01/2021