

POLE BRACKET • For mounting one fixture on an existing pole			
<p>60mm(2 3/8in.) 183.6mm(7.28in.) 76mm(3in.) 102±1mm(4in.)</p>	<p>4" Square Pole Mount with 2-3/8" O.D. Tenon JM4SQ-SP-D Finish: Dark Bronze USE: For use with square, non-tapered steel and aluminum poles. Furnished with four 5/16" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p>	<p>60mm(2 3/8in.) 222.5mm(8.76in.) 101.6mm(4in.) 106.68mm(4.2in.)</p>	<p>4" Round Pole Mount with 2-3/8" O.D. Tenon JM4SQR-SP-D Finish: Dark Bronze USE: For use with Round, non-tapered steel and aluminum poles. Furnished with three 3/8" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p>
<p>60mm(2 3/8in.) 183.6mm(7.28in.) 76mm(3in.) 127±1mm(5in.)</p>	<p>5" Square Pole Mount with 2-3/8" O.D. Tenon JM5SQ-SP-D Finish: Dark Bronze USE: For use with square, non-tapered steel and aluminum poles. Furnished with four 5/16" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p>	<p>60mm(2 3/8in.) 222.5mm(8.76in.) 101.6mm(4in.) 131.86mm(5.19in.)</p>	<p>5" Round Pole Mount with 2-3/8" O.D. Tenon JM5SQR-SP-D Finish: Dark Bronze USE: For use with Round, non-tapered steel and aluminum poles. Furnished with three 3/8" hex head stainless-steel bolts. Vertical tenon measures 2-3/8" O.D., and is made of steel tubing. Fixtures mounted to this bracket can be adjusted both vertically and horizontally.</p>
<p>154.5±1mm(6.08 in.) 102±1mm(4 in.) 106.6mm(4.28in.) 63mm(2.48in.)</p>	<p>Pole Bracket accessories-Tenon & Yoke Adaptor JMSP-TR-D Finish: Dark Bronze USE: The 2-3/8" OD Tenon Mount Adaptor for Yoke Fixtures is designed to mount MESTER light fixtures that are equipped with a yoke mount onto a 2-3/8" OD tenon. It may be utilized with the Mester Flood Light Series of light fixtures.</p>		
WALL BRACKET • Attaches to any flat surface • Provides wiring access		Mid-Pole tenon Bracket	
<p>60mm(2 3/8in.) 102±1mm(4in.) 227.2mm(7.76 in.) 152.4mm(6in.)</p>	<p>90° Wall Mount Bracket with 2-3/8" O.D. Tenon JMWM-SP-D Finish: Dark Bronze USE: The 90° wall mount bracket with 2-3/8" tenon attaches an MESTER floodlight to almost any surface: wall, roof, or wood pole. Provides wiring access and abuilt-in 2-3/8" O.D. tenon to mount a fixture with our adjustable slipfitter. Suggested 3/8" diameter bolts for mounting. Mounting holes are spaced 3-1/4" apart.</p>	<p>185mm(7.28in.) 180mm(7.09 in.) 102mm(3.74 in.) 60mm(2.38 in.)</p>	<p>2-3/8" OD Horizontal Tenon Mid-Pole Bracket JM5Q-SP-D Finish: Dark Bronze USE: 2-3/8" OD Horizontal Tenon Mid-Pole Bracket is designed to mount light fixture that is equipped with a adjustable slipfitter onto a 2-3/8" OD horizontal tenon</p>
Round External Mount Horizontal Tenon • To mount 2/3/4 fixtures on a existing pole			
<p>180mm(7.25in.) 101.6mm(4in.) 60mm(2.38in.) 63.5mm(2.5in.)</p>	<p>Double 90° Horizontal Tenon Adaptor JMR60-SP2-90-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Two fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally</p>	<p>180mm(7.25in.) 101.6mm(4in.) 60mm(2.38in.) 63.5mm(2.5in.)</p>	<p>Triple 120° Horizontal Tenon Adaptor JMR60-SP3-120-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Three fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally</p>
<p>180mm(7.25in.) 101.6mm(4in.) 60mm(2.38in.) 63.5mm(2.5in.)</p>	<p>Double 180° Horizontal Tenon Adaptor JMR60-SP2-180-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Two fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally</p>	<p>180mm(7.25in.) 101.6mm(4in.) 60mm(2.38in.) 63.5mm(2.5in.)</p>	<p>Quad 90° Horizontal Tenon Adaptor JMR60-SP4-90-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Four fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally</p>
<p>180mm(7.25in.) 101.6mm(4in.) 60mm(2.38in.) 63.5mm(2.5in.)</p>	<p>Triple 90° Horizontal Tenon Adaptor JMR60-SP3-90-D Finish: Dark Bronze USE: The Bracket is designed to mount over 2-3/8" (60mm) O.D. vertical tenon. Three fixtures can be mounted to the Round External Mount Horizontal Tenon and adjusted horizontally</p>		