

JIL-SM-1303 SERIES

ARCHITECTURAL LINEAR LUMINAIRES



FLEXIBLE SURFACE MOUNTED PROFILE

Introducing the **JIL SERIES** our premium local auxiliary lighting system designed to elevate interior spaces with a touch of sophistication. This versatile system is perfect for various interior decoration scenarios and localized lighting spaces, creating unique atmospheres and visual enjoyment beyond basic illumination.



Standard Features

- **Dot-free Lighting:** Experience perfect homogenous lighting that adds a seamless glow to your surroundings.
- **Various Diffuser Options:** Choose from a range of diffuser options in different shapes and light distribution plans, providing complete solutions for your lighting needs.
- **UGR Rating:** Glare rating 10
- **End Caps:** Tailor the wire outgoing to your preference with two end cap options. The close-fitting design, without screws, ensures easy installation for a polished look.
- **Various Installation Methods:** Explore a wide array of installation accessories for broader applications, adapting the system to diverse spaces effortlessly.
- **One-Cut System:** Maintain a consistent length between the diffuser and profile for a sleek and uniform appearance.
- **Smart Control for Unlimited Possibilities:** Experience personalized lighting control with the ability to seamlessly match profiles. Control the ambiance with a simple hand sweep or touch, unlocking endless possibilities for customization.

PROFILE DIMENSIONS



FLEXIBLE ALUMINUM ALLOY



Quotations: quotes@jademar.com
To place an order: orders@jademar.com
Tel: (305) 640.0465 | Fax: (305) 640.0468
WWW.JADEMAR.COM



Information contained herein is subject to change without notice.
Revised 07/2025

SINGLE RUN LUMINAIRE: SPECIFICATION AND SUBMITTAL SHEET



PROJECT NAME:

LOCATION:

SPECIFYING ARCHITECT:

CONTACT NAME:

REP AGENCY:

APPROVAL BY:

DATE:

CONTACT EMAIL:

STEP 1

SELECT PROFILE TYPE ORDERING EXAMPLE: **JIL-SM-1303-FA-4FT-ST-24V-35K-300L-90-DL-S-RS-E12-IP68**

PROFILE SERIES	ASSEMBLY	LENGTH	Output	LIGHT SOURCE	LUMEN/FT	CRI	DIFFUSER TYPE
JIL-SM-1303	FA Field Assembly FM Factory Made	4FT 5FT 6FT 7FT 8FT	ST-24V Standard 24V HO-48V High Output 48V	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K 60K 6000K	xL Replace "x" with the desired lumen/ft	90 90CRI	DL Diffused Lens

Max length of
extrusion: 98" (8ft)

PROFILE COLOR	MOUNTING OPTIONS	POWER FEED POSITION/LENGTH	IP PROTECTION
S Silver (RAL9006) B Black (RAL9005) W White (RAL9003)	RS Recessed/Surface Mount Clips Set	Ex End Feed Wire Replace "x" with desired power feed wire length	Blank No IP68 Connector IP68 with IP68 Connector

POWER FEED OPTIONS



STEP 2

SELECT A DRIVER (REQUIRED)
Refer to driver brochure [online](#)

STEP 3

SELECT CONTROL OPTIONS
Refer to control options page [online](#)


TruBlu
SILVAIR

CASAMBI

LIGHT SOURCE LUMEN ELECTRICAL DATA

Light Source	Input Voltage	CRI	Current /ft	Power /ft	Average lm/W	Max Length	Cut Length	LED Pitch	Min Bend ø	Mounting Type	Delivered Lumens/ft					
											2300K	2700K	3000K	3500K	4000K	6000K
Standard	DC24V	>90	122mA	3W	118W	32.8FT	0.33"	0.33"	ø2.36"	3M TAPE	269	310	322	322	317	307
High Output	DC24V	>90	212mA	5W	116W	32.8FT	0.13"	0.13"	ø2.36"	3M TAPE	500	512	536	545	548	528





JIL-SM-1303 SERIES

ARCHITECTURAL LINEAR LUMINAIRES

FLEXIBLE SURFACE MOUNTED PROFILE

SEAMLESS CONTINUOUS RUN: SPECIFICATION AND SUBMITTAL SHEET

PROJECT NAME:

LOCATION:

SPECIFYING ARCHITECT:

CONTACT NAME:

REP AGENCY:

APPROVAL BY:

DATE:

CONTACT EMAIL:

STEP 1

SELECT PROFILE TYPE ORDERING EXAMPLE: **JIL-SM-1303-FA-4FT-ST-24V-35K-300L-90-DL-S-RS-E12-IP68**

PROFILE SERIES	ASSEMBLY	RUN LENGTH	Output	LIGHT SOURCE	LUMEN/FT	CRI	DIFFUSER TYPE
JIL-SM-1303	FA Field Assembly FM Factory Made	x Replace "x" with required run length in FT or Inches. Max length of each extrusion: 98" (8ft)	ST-24V Standard 24V HO-48V High Output 48V	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K 60K 6000K	xL Replace "x" with the desired lumen/ft	90 90CRI	DL Diffused Lens
PROFILE COLOR	MOUNTING OPTIONS	POWER FEED POSITION/LENGTH	IP PROTECTION				
S Silver (RAL9006) B Black (RAL9005) W White (RAL9003)	RS Recessed/Surface Mount Clips Set	Ex End Feed Wire Bx Back Feed Wire	Blank No IP68 Connector IP68 with IP68 Connector				

Replace "x" with desired
power feed wire length

POWER FEED OPTIONS



STEP 2

SELECT A DRIVER (REQUIRED)
Refer to driver brochure [online](#)

STEP 3

SELECT CONTROL OPTIONS
Refer to control options page [online](#)

TruBlu
SILVAIR

CASAMBI

LIGHT SOURCE LUMEN ELECTRICAL DATA


Light Source	Input Voltage	CRI	Current /ft	Power /ft	Average lm/W	Max Length	Cut Length	LED Pitch	Min Bend ø	Mounting Type	Delivered Lumens/ft					
											2300K	2700K	3000K	3500K	4000K	6000K
Standard	DC24V	>90	122mA	3W	118W	32.8FT	0.33"	0.33"	ø2.36"	3M TAPE	269	310	322	322	317	307
High Output	DC24V	>90	212mA	5W	116W	32.8FT	0.13"	0.13"	ø2.36"	3M TAPE	500	512	536	545	548	528



Quotations: quotes@jademar.com
To place an order: orders@jademar.com
Tel: (305) 640.0465 | Fax: (305) 640.0468
WWW.JADEMAR.COM



Information contained herein is subject to change without notice.
Revised 07/2025




JIL-SM-1303 SERIES

ARCHITECTURAL LINEAR LUMINAIRES
FLEXIBLE SURFACE MOUNTED PROFILE

SHOP DRAWING

1FT



PROJECT NOTES



Quotations: quotes@jademar.com
To place an order: orders@jademar.com
Tel: (305) 640.0465 | Fax: (305) 640.0468
WWW.JADEMAR.COM



Information contained herein is subject to change without notice.
Revised 07/2025