

JIL-RM-2507 SERIES

ARCHITECTURAL LINEAR LUMINAIRES



RECESSED AND MILLWORK PROFILE

Introducing the **JIL SERIES** our premium local auxiliary lighting system designed to elevate interior spaces with a touch of sophistication. This versatile system is perfect for various interior decoration scenarios and localized lighting spaces, creating unique atmospheres and visual enjoyment beyond basic illumination.


Standard Features

- **Dot-free Lighting:** Experience perfect homogenous lighting that adds a seamless glow to your surroundings.
- **Various Diffuser Options:** Choose from a range of diffuser options in different shapes and light distribution plans, providing complete solutions for your lighting needs.
- **UGR Rating:** Glare rating 10
- **End Caps:** Tailor the wire outgoing to your preference with two end cap options. The close-fitting design, without screws, ensures easy installation for a polished look.
- **Various Installation Methods:** Explore a wide array of installation accessories for broader applications, adapting the system to diverse spaces effortlessly.
- **One-Cut System:** Maintain a consistent length between the diffuser and profile for a sleek and uniform appearance.
- **Smart Control for Unlimited Possibilities:** Experience personalized lighting control with the ability to seamlessly match profiles. Control the ambiance with a simple hand sweep or touch, unlocking endless possibilities for customization.

PROFILE DIMENSIONS



RECESSED



FINISHED LOOK



APPLICATION



Quotations: quotes@jademar.com
 To place an order: orders@jademar.com
 Tel: (305) 640.0465 | Fax: (305) 640.0468
WWW.JADEMAR.COM



Jademar Lighting has prepared the information contained in this document with due care. However, Jademar Lighting does not warrant or represent that the information is free from errors or omission. While the information is considered to be true and correct at the date of publication, changes in circumstances after that date may impact on its accuracy. The information may change without notice and Jademar Lighting is not liable for the accuracy of any information printed and stored or interpreted or used.

SINGLE RUN LUMINAIRE: SPECIFICATION AND SUBMITTAL SHEET



PROJECT NAME:

LOCATION:

SPECIFYING ARCHITECT:

CONTACT NAME:

REP AGENCY:

APPROVAL BY:

DATE:

CONTACT EMAIL:

STEP 1

SELECT PROFILE TYPE ORDERING EXAMPLE: **JIL-RM-2507-FA-4FT-ST-24V-35K-300L-90-DL-S-RS-E12-IP68**

JIL-RM-2507						
PROFILE SERIES	ASSEMBLY	LENGTH	Output	LIGHT SOURCE	LUMEN/FT	CRI
JIL-RM-2507	FA Field Assembly FM Factory Made	4FT 5FT 6FT 7FT 8FT	ST-24V Standard 24V HO-48V High Output 48V	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K 60K 6000K	xL Replace "x" with the desired lumen/ft	90 90CRI

Max length of
extrusion: 98" (8ft)

DIFFUSER TYPE	PROFILE COLOR	MOUNTING OPTIONS	POWER FEED POSITION/LENGTH	IP PROTECTION
DL Diffused Lens	S Silver (RAL9006) B Black (RAL9005) W White (RAL9003)	RM Recessed Mount Clips Set	Ex End Feed Wire Bx Back Feed Wire Tx Top Feed Wire	Blank No IP68 Connector IP68 with IP68 Connector

Replace "x" with desired
power feed wire length

POWER FEED OPTIONS



STEP 2

SELECT A DRIVER (REQUIRED)

Refer to driver brochure [online](#)

STEP 3

SELECT CONTROL OPTIONS

Refer to control options page [online](#).

SILVAIR **CASAMBI**

LIGHT SOURCE LUMEN ELECTRICAL DATA

Light Source	Input Voltage	CRI	Current /ft	Power /ft	Average lm/W	Max Length	Cut Length	LED Pitch	Min Bend ø	Mounting Type	Delivered Lumens/ft					
											2300K	2700K	3000K	3500K	4000K	6000K
Standard	DC24V	>90	122mA	3W	118W	32.8FT	0.33"	0.33"	ø2.36"	3M TAPE	269	310	322	322	317	307
High Output	DC24V	>90	212mA	5W	116W	32.8FT	0.13"	0.13"	ø2.36"	3M TAPE	500	512	536	545	548	528



SEAMLESS CONTINUOUS RUN: SPECIFICATION AND SUBMITTAL SHEET

PROJECT NAME:

LOCATION:

SPECIFYING ARCHITECT:

CONTACT NAME:

REP AGENCY:

APPROVAL BY:

DATE:

CONTACT EMAIL:

STEP 1

SELECT PROFILE TYPE ORDERING EXAMPLE: **JIL-RM-2507-FA-4FT-ST-24V-35K-300L-90-DL-S-RS-E12-IP68**

JIL-RM-2507						
PROFILE SERIES	ASSEMBLY	RUN LENGTH	Output	LIGHT SOURCE	LUMEN/FT	CRI
JIL-RM-2507	FA Field Assembly FM Factory Made	x Replace "x" with required run length in FT or Inches. Max length of each extrusion: 98" (8ft)	ST-24V Standard 24V HO-48V High Output 48V	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K 60K 6000K	xL Replace "x" with the desired lumen/ft	90 90CRI
DIFFUSER TYPE	PROFILE COLOR	MOUNTING OPTIONS	POWER FEED POSITION/LENGTH	IP PROTECTION		
DL Diffused Lens	S Silver (RAL9006) B Black (RAL9005) W White (RAL9003)	RM Recessed Mount Clips Set	Ex End Feed Wire Bx Back Feed Wire Tx Top Feed Wire	Blank No IP68 Connector IP68 with IP68 Connector		

Replace "x" with desired
power feed wire length

POWER FEED OPTIONS



STEP 2

SELECT A DRIVER (REQUIRED)

Refer to driver brochure [online](#)

STEP 3

SELECT CONTROL OPTIONS


Refer to control options page [online](#)

SILVAIR CASAMBI

LIGHT SOURCE LUMEN ELECTRICAL DATA

Light Source	Input Voltage	CRI	Current /ft	Power /ft	Average lm/W	Max Length	Cut Length	LED Pitch	Min Bend ø	Mounting Type	Delivered Lumens/ft					
											2300K	2700K	3000K	3500K	4000K	6000K
Standard	DC24V	>90	122mA	3W	118W	32.8FT	0.33"	0.33"	ø2.36"	3M TAPE	269	310	322	322	317	307
High Output	DC24V	>90	212mA	5W	116W	32.8FT	0.13"	0.13"	ø2.36"	3M TAPE	500	512	536	545	548	528






JIL-RM-2507 SERIES

ARCHITECTURAL LINEAR LUMINAIRES
RECESSED AND MILLWORK PROFILE

SHOP DRAWING

1FT



PROJECT NOTES



Quotations: quotes@jademar.com
To place an order: orders@jademar.com
Tel: (305) 640.0465 | Fax: (305) 640.0468
WWW.JADEMAR.COM



Jademar Lighting has prepared the information contained in this document with due care. However, Jademar Lighting does not warrant or represent that the information is free from errors or omission. While the information is considered to be true and correct at the date of publication, changes in circumstances after that date may impact on its accuracy. The information may change without notice and Jademar Lighting is not liable for the accuracy of any information printed and stored or interpreted or used.