

JADIL-25-ML SERIES

MICRO LOUVER DIRECT ONLY OR
DIRECT/INDIRECT CCT, POWER &
DIRECT/INDIRECT LIGHT
DISTRIBUTION SELECTABLE BUILT-IN

PRODUCT FEATURES

CONSTRUCTION

- Black, white, silver gray, and any other custom-specified RAL finish
- An independent LED uplighting module is available
- Custom patterns with optional L, X and T joiners
- Strong, durable formula for long-lasting color retention
- The diffuser and die-cast aluminum endcaps at the fixture ends overlap to eliminate gaps and visible LEDs

OPTICS

- 5 options of indirect and direct light distributions can be set by dip switch
- Direct Optics: Anti Glare Micro Louver

ELECTRICAL

- Power Selectable: 2Ft (20W/15W/10W); 4Ft (40W/30W/20W); 6Ft (60W/45W/30W); 8Ft (80W/60W/40W)
- Input Voltage: CC 120-277VAC Internal driver
- CCT Selectable: 2700K/3000K/3500K/4000K/5000K
- Efficacy: up to 135 lm/W
- Power Factor: >0.90
- CRI: 80 Standard / 90 Optional
- Operating Temp: -4°F to 104°F (-20°C to 40°C)
- Total Harmonic Distortion: <20%

DIMMING & CONTROLS

- 0-10V Dimming Standard
- PIR Sensor Optional
- Bluetooth Controller or Bluetooth Sensor Optional
- Emergency Battery Optional


MOUNTING

- Drywall-hard ceiling pendant mount
- Drop ceiling pendant mount
- Surface mount
- Wall mount
- Trimless Recessed mount kit - Hard ceiling: 2ft / 4ft / 8ft
- Recessed mount with flange kit - Hard ceiling: 2ft / 4ft / 8ft
- T-Grid recessed mount

RATINGS & CERTIFICATIONS

- UL
- Rohs
- Natatorium Rated
- CCEA (City of Chicago Environmental Air)

Lifetime Based on TM21: L70 179,000 L80 149,000 L90 132,000



SPECIFICATIONS

Input Power	2Ft (20W/15W/10W); 4Ft (40W/30W/20W); 6Ft (60W/45W/30W); 8Ft (80W/60W/40W)
Efficacy	up to 135 lm/W
CRI	80 Standard / 90 Optional
CCT	Selectable: 2700K/3000K/3500K/4000K/5000K
Input Voltage	CC 120-277VAC Internal driver
Dimming & Controls	0-10V Dimming Standard / PIR Sensor / Bluetooth Controller or Bluetooth Sensor Optional / EM Battery Optional
Ingress Protection	IP20 for Damp Locations
Mounting	Standard: Drywall-hard ceiling pendant mount Optional: Drop ceiling pendant mount Surface mount Wall mount Trimless Rec. mount kit - Hard ceiling: 2ft / 4ft / 8ft Rec. mount w/ flange kit - Hard ceiling: 2ft / 4ft / 8ft T-Grid recessed mount
Lifetime Based on TM21	L70 179,000 L80 149,000 L90 132,000
Limited Warranty	10 Years


DIMENSIONS

Item	Length (L)		Width (W)		Height (H)	
	Inches (in)	Metric (mm)	Inches (in)	Metric (mm)	Inches (in)	Metric (mm)
JADIL-25-ML-D-CPS2-20W	23.62	600	2.48	63	3.15	80
JADIL-25-ML-D-CPS4-40W	47.24	1,200	2.48	63	3.15	80
JADIL-25-ML-D-CPS6-60W	70.87	1,800	2.48	63	3.15	80
JADIL-25-ML-D-CPS8-80W	94.49	2,400	2.48	63	3.15	80

Continuous Run

120VAC: Connections up to 40ft / 277VAC: Connections up to 100ft


Connectors' shapes available (for Diffuser only): L, T, X, Y, V



Quotations: quotes@jademar.com
To place an order: orders@jademar.com
Tel: (305) 640.0465 | Fax: (305) 640.0468
WWW.JADEMAR.COM



Jademar Lighting has prepared the information contained in this document with due care. However, Jademar Lighting does not warrant or represent that the information is free from errors or omission. While the information is considered to be true and correct at the date of publication, changes in circumstances after that date may impact on its accuracy. The information may change without notice and Jademar Lighting is not liable for the accuracy of any information printed and stored or interpreted or used. Revised 07/2026



SPECIFICATION SUBMITTAL DETAIL

Project Name/Type:		Date:
Catalog/Part #:		

JADIL-25-ML SERIES MICRO LOUVER CCT, POWER & DIRECT/INDIRECT LIGHT DISTRIBUTION SELECTABLE BUILT-IN

Ordering Information / Example: **JADIL-25-ML-D-CPS6-L-1PD-DWP-2-WH-BPOS-EM-4W**

JADIL-25-ML							
Product Series	Lighting Direction	CCT & Power, Length	Input Voltage	CRI	Lens/Diffuser	Dimming & Tuning	Mounting Options
JADIL-25-ML	D Direct	CPS2 27/30/35/40/50K, 20W/15W/10W, 2' Linear CPS4 27/30/35/40/50K, 40W/30W/20W, 4' Linear CPS6 27/30/35/40/50K, 60W/45W/30W, 6' Linear CPS8 27/30/35/40/50K, 80W/60W/40W, 8' Linear CPS-XX-XXW-XXK XX: Length / XXW: Watts/Unit/ XXK: CCT Factory set	Blank 120-277VAC	Blank 80 CRI 90 90 CRI	Blank Anti Glare Micro Louver Standard	D 0-10 down to 5% Dim 1PD 1% Dim DW Dim to warm TW 0-10V Tunable white 1% Linear DALI DALI2 Tunable white 0.1% Linear	DWP-XX Drywall-hard ceiling pendant mount, XX' cable DCP-XX Drop ceiling pendant mount, XX' cable SM Surface mount WM Wall mount TR Trimless Recessed mount kit R-XX Recessed mount with flange kit TGR T-Grid recessed mount DWP-XX Drywall-hard ceiling pendant mount, XX' cable DCP-XX Drop ceiling pendant mount, XX' cable WM Wall mount
DI Direct/Indirect					Blank Anti Glare Micro Louver Standard		

Housing Color	Control Options	Emergency Battery Backup
WH White (Standard) BK Black S Silver CC Replace CC with RAL code	Blank No sensor/controls BPOS BI-level PIR Occ. Sensor SR-NLC-MWS Silvar Microwave Sensor Integral Magnet Mount CB-NLC-MWS Casambi Microwave Sensor Integral Magnet Mount BN-NLC-MWS Bubblynet Microwave Sensor Integral Magnet Mount SR-NLC-FC Silvar Fixture Controller, 12-24VDC, 0-10 Volt Dimming with sensor input CB-NLC-FC Casambi Fixture Controller, 12-24VDC, 0-10 Volt Dimming with sensor input BN-NLC-FC Bubblynet Fixture Controller, 12-24VDC, 0-10 Volt Dimming with sensor input	EM-4W 4W EM Pack EM-8W 8W EM Pack EM-15W 15W EM Pack *Only 4ft, 6ft & 8ft units come with integral EM battery packs.

PERFORMANCE AND ELECTRICAL DATA

Product Name	JADIL-25-ML-CPS2			JADIL-25-ML-CPS4			JADIL-25-ML-CPS6			JADIL-25-ML-CPS8		
Length	2 Feet			4 Feet			6 Feet			8 Feet		
Setting	Lv1	Lv2	Lv3	Lv1	Lv2	Lv3	Lv1	Lv2	Lv3	Lv1	Lv2	Lv3
Wattage	20W	15W	10W	40W	30W	20W	60W	45W	30W	80W	60W	40W
2700K (80CRI) Total Lumens / Lumens per Watt	2500 lm / 125 lm/W	1875 lm / 125 lm/W	1250 lm / 125 lm/W	5000 lm / 125 lm/W	3750 lm / 125 lm/W	2500 lm / 125 lm/W	7500 lm / 125 lm/W	5625 lm / 125 lm/W	3750 lm / 125 lm/W	10000 lm / 125 lm/W	7500 lm / 125 lm/W	5000 lm / 125 lm/W
3000K (80CRI) Total Lumens / Lumens per Watt	2500 lm / 125 lm/W	1875 lm / 125 lm/W	1250 lm / 125 lm/W	5000 lm / 125 lm/W	3750 lm / 125 lm/W	2500 lm / 125 lm/W	7500 lm / 125 lm/W	5625 lm / 125 lm/W	3750 lm / 125 lm/W	10000 lm / 125 lm/W	7500 lm / 125 lm/W	5000 lm / 125 lm/W
3500K (80CRI) Total Lumens / Lumens per Watt	2700 lm / 135 lm/W	2025 lm / 135 lm/W	1350 lm / 135 lm/W	5400 lm / 135 lm/W	4050 lm / 135 lm/W	2700 lm / 135 lm/W	8100 lm / 135 lm/W	6075 lm / 135 lm/W	4050 lm / 135 lm/W	10800 lm / 135 lm/W	8100 lm / 135 lm/W	5400 lm / 135 lm/W
4000K (80CRI) Total Lumens / Lumens per Watt	2700 lm / 135 lm/W	2025 lm / 135 lm/W	1350 lm / 135 lm/W	5400 lm / 135 lm/W	4050 lm / 135 lm/W	2700 lm / 135 lm/W	8100 lm / 135 lm/W	6075 lm / 135 lm/W	4050 lm / 135 lm/W	10800 lm / 135 lm/W	8100 lm / 135 lm/W	5400 lm / 135 lm/W
5000K (80CRI) Total Lumens / Lumens per Watt	2600 lm / 130 lm/W	1950 lm / 130 lm/W	1300 lm / 130 lm/W	5200 lm / 130 lm/W	3900 lm / 130 lm/W	2600 lm / 130 lm/W	7800 lm / 130 lm/W	5850 lm / 130 lm/W	3900 lm / 130 lm/W	10400 lm / 130 lm/W	7800 lm / 130 lm/W	5200 lm / 130 lm/W
Number of Drivers	1	1	1	1	1	1	1	1	1	1	1	1
Driver Current (mA)	430	430	430	850	850	850	1300	1300	1300	1700	1700	1700
Current (A) @ 120V	0.17	0.13	0.08	0.33	0.25	0.17	0.5	0.38	0.25	0.67	0.5	0.33
Current (A) @ 208V	0.1	0.07	0.05	0.19	0.14	0.1	0.29	0.22	0.14	0.38	0.29	0.19
Current (A) @ 240V	0.08	0.06	0.04	0.17	0.13	0.08	0.25	0.19	0.13	0.33	0.25	0.17
Current (A) @ 277V	0.07	0.05	0.04	0.14	0.11	0.07	0.22	0.16	0.11	0.29	0.22	0.14

Note: All parameters are based on the frosted diffuser




Quotations: quotes@jademar.com
To place an order: orders@jademar.com
Tel: (305) 640.0465 | Fax: (305) 640.0468
WWW.JADEMAR.COM



Jademar Lighting has prepared the information contained in this document with due care. However, Jademar Lighting does not warrant or represent that the information is free from errors or omission. While the information is considered to be true and correct at the date of publication, changes in circumstances after that date may impact on its accuracy. The information may change without notice and Jademar Lighting is not liable for the accuracy of any information printed and stored or interpreted or used. Revised 07/2026


SELECTABLE WATTAGE, CCT AND LIGHT DISTRIBUTION




Field Adjustable Power Out-Put



Field Adjustable CCT





Field Adjustable Direct/Indirect Light Distribution



OPTICS

JADIL-25-ML



Micro Louver (UGR<19)



JADIL-25-ML SERIES

MICRO LOUVER DIRECT ONLY OR DIRECT/INDIRECT CCT, POWER & DIRECT/INDIRECT LIGHT DISTRIBUTION SELECTABLE BUILT-IN

BLUETOOTH® FUNCTIONS

Driver and Control Solution

Tunable white W/ BLE mesh for linear fixture

Bluetooth Linear:

Bluetooth mesh driver, ready for commissioning immediately after installation.

Lumen and CCT Control:

CCT & lumen adjustable, up and down distribution adjustable. Wireless control via wall switch or App.

Motion Sensor

Bluetooth motion sensor for standard linears and an eco sensor for Bluetooth linears.

Control Mode

Bluetooth Wall Switch:

5-Key, battery operated wall switch. Battery life estimated 3+ years. Works with bluetooth motion sensor or bluetooth linears.


APP Bluetooth Linear:

A free commissioning/control app is incl




PLUG-IN PIR SENSOR

The optional receptacle for plug-and-play sensor eliminates the need for on-site modifications, making installation quick and hassle-free.




MOUNTING OPTIONS


Drywall-hard ceiling
pendant mount




Drop Ceiling Pendant Mount




Surface Mount




Wall Mount




Trimless Recessed Mount






Recessed Mount



T-Grid Recessed Mount



MOUNTING ACCESSORIES

1 DROP CEILING PENDANT MOUNT KIT 	3 6C POWER CORD KIT 
2 DRY WALL PENDANT MOUNT KIT 	5 SURFACE MOUNT KIT 
4 STRAIGHT CONNECTOR KIT 	7 HARD/DRYWALL CEILING RECESSED MOUNT KIT 
6 WALL MOUNT KIT 	

(Cables/cords factory installed on each unit unless requested otherwise)



MOUNTING ACCESSORIES

8 TRIMLESS RECESSED MOUNT KIT 	9 T-GRID RECESSED MOUNT KIT 
10 40FT DIFFUSER 	11 L JOINER 
12 X JOINER 	13 T JOINER 

